

Model: SP60G Series

Features

- Universal AC input 90~264Vac.
- 4" x 2" miniature size.
- Operation from -20°C ~ 50°C full load.
- Protections: SCP / OVP / OLP..
- No load power consumption < 0.75W.
- 105°C Main electrolytic capacitor.

Specifications

Approvals



Size

101.6 * 50.8 * 30 mm(L*W*H)



Model No		SP60G-33	SP60G-05	SP60G-12	SP60G-15	SP60G-24	SP60G-48
Output	DC Voltage	3.3V	5V	12V	15V	24V	48V
	Rated Current	0-10A	0-10A	0-5A	0-4A	0-2.5A	0-1.25A
	Rated Power	33W	50W	60W	60W	60W	60W
	Ripple & Noise (Max.) Note.2	80mV	80mV	120mV	150mV	200mV	300mV
	Efficiency (Typ.)	76%	80%	83%	84%	85%	86%
	Voltage Adjustment Range	3.15-3.45V	4.8-5.2V	11.4-12.6V	14.2-16V	23-25V	45-51V
	Voltage Tolerance Note.3	±2%	±2%	±2%	±2%	±1%	±1%
	Rise Time	<30ms at full load.					
	Set up time (Max.)	500ms/230Vac, 500ms/115Vac, at cold first start.					
Hold Time (Typ.)	60ms/230Vac, 13ms/115Vac at full load.						
Input	Voltage Range	90Vac ~ 264Vac or 127~370Vdc.					
	Frequency Range	47 ~ 63 Hz.					
	AC Current (Max.)	1.5A at 115Vac / 1A at 230Vac.					
	Inrush Current (Max.)	30A at 115Vac / 60A at 230Vac (COLD START).					
	Leakage Current	<0.75mA / 240Vac.					
Protections	Over Load	115~150% rated output power. Type: Hiccup mode, Recovers automatically after fault condition is removed.					
	Short Circuit	Type: Hiccup mode, Recovers automatically after fault condition is removed.					
	Over Voltage	3.8-4.3V	5.75-6.5V	13.5-15V	16.9-18.75V	27-30V	54-60V
Environment	Operation Temp.	-20°C ~50°C full load, 50°C ~70°C (Refer to output load derating curve).					
	Operation Humidity	20% ~ 95% RH non-condensing.					
	Storage Temp.	-40 ~ +80°C.					
	Storage Humidity	10% ~ 90% RH.					
	Vibration	10~500 Hz, 2G 10 min./1 cycle, period for 60 min. each along X, Y, Z axes.					

Mechanical Specification

