



## DT-M090A Medical Application Series

Meet CEC , DoE Level VI, Energy Star, ErP Stage 2  
No Load Power Consumption Less Than 0.15W



### Features :

- ANSI/AAMI/IEC/EN ES60601-1:2012 (60601 edition 3.1)
- EMC : IEC60601-1-2 : 2014 (edition 4.0)
- IEC 60950 approval
- Means of Protection: 2 X MOPP
- Touch Current : < 100µA
- 100-240VAC Universal Input
- Single Output to 90W
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Private Label Marking Available
- Modified and Custom Design Available
- 2 Years Warranty

## Medical Desktop Power Supply

Model	Output Voltage	Output Current	Power
DT-M090A-120-X-XX	12.0V	7.00A	84.00W
DT-M090A-150-X-XX	15.0V	6.00A	90.00W
DT-M090A-180-X-XX	18.0V	5.00A	90.00W
DT-M090A-190-X-XX	19.0V	4.74A	90.00W
DT-M090A-240-X-XX	24.0V	3.75A	90.00W
DT-M090A-480-X-XX	48.0V	1.88A	90.00W

Available input plug options are:

U = C8, W = C6, V=C14, S=C18

