



DT-M120A Medical Application Series

Meet CEC , Energy Star Level V , ErP Stage 2
NO Load Power Consumption Less Than 0.5W



- Features :**
- ANSI/AAMI/IEC/EN ES60601-1:2005 (60601 3rd edition)
 - IEC 60950 approval
 - Means of Protection: 2 X MOPP
 - Touch Current : < 100µA
 - 100-240VAC Universal Input
 - Single Output to 120W
 - Regulated Output With Low Ripple Noise
 - Safety Agency Requirements and EMI/EMS Certified
 - Private Label Marking Available
 - Modified and Custom Design Available
 - 2 Years Warranty

Medical Desktop Power Supply

Model	Output Voltage	Output Current	Power
DT-M120A-120-X-XX	12.0V	10.00A	120.00W
DT-M120A-150-X-XX	15.0V	8.00A	120.00W
DT-M120A-180-X-XX	18.0V	6.60A	120.00W
DT-M120A-190-X-XX	19.0V	6.32A	120.00W
DT-M120A-240-X-XX	24.0V	5.00A	120.00W
DT-M120A-360-X-XX	36.0V	3.34A	120.00W
DT-M120A-480-X-XX	48.0V	2.50A	120.00W

Available input plug options are:

U = C8, W = C6, V=C14, S=C18

