Sales / Technical Support: +1-818-338-7788 Option 3
Email: sales@autecpower.com

WM-M012A-XXX-TP1-X Medical Application Series

Meet CEC, DoE Level VI, Energy Star, ErP Stage 2, NRCan & GEMS
No Load Power Consumption Less 0.075W

Features :

- ANSI/AAMI/IEC/EN ES60601-1:2012 (60601 edition 3.1)
- EMC : IEC60601-1-2 : 2014 (edition 4.0)
- IEC 60950 approval
- Means of Protection: 2 X MOPP
- Touch Current : < 100μA
  < 10μA (Optional)
- 100-240VAC Universal Input
- Single Output to 12W
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Private Label Marking Available
- Modified and Custom Design Available
- 2 Years Warranty

Wall Mount Medical Power Supply with Interchangeable A/C Input Blade Travel Kit

Offered with attached cable & connector, and also as in internal USB Port on the power supply as an option. Please contact the factory for your CALL-OUT!

Model	Output Voltage	Output Current	Power
WM-M012A-033-TP1-XX	3.3V	2.00A	6.60W
WM-M012A-050-TP1-XX	5.0V	2.00A	10.00W
WM-M015A-050-TP1-XX	5.0V	3.00A	15.00W
WM-M012A-059-TP1-XX	5.9V	2.00A	11.80W
WM-M012A-062-TP1-XX	6.2V	2.00A	12.40W
WM-M012A-090-TP1-XX	9.0V	1.20A	10.80W
WM-M012A-120-TP1-XX	12.0V	1.00A	12.00W
WM-M012A-150-TP1-XX	15.0V	0.67A	12.00W
WM-M012A-180-TP1-XX	18.0V	1.36A	12.06W
WM-M012A-240-TP1-XX	24.0V	0.50A	12.00W