





Input	
Voltage	100-240VAC
Line Frequency	50-60Hz
Current	0.31A-0.17A
Protection	Internal Primary Current Fuse , Inrush Limiting
Configuration	A for US Plug
	D for EU Plug
	C for UK Plug

Output	
Load Regulation	±5% ( Typical )
Ripple	1 ~ 2% Vp-p Max. for Output Voltage @ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection
DC Cord	22AWG / 20AWG / 18AWG
Ferrite Core	Yes

Safety Approvals	
For USA - UL / cUL / FCC	
For Europe & UK - CE	

Electrical	
Topology	Switching Flyback
Dielectric Withstand	4000VAC Primary - Secondary
Touch Current	< 100µA
Efficiency	Energy Star Level V, ErP Stage 2, NRCan & GEMS Certified
EMI Conduction & Radiation	Compliance to EN55011 Class B
Harmonic Current	Compliance to EN61000-3-2, 3
EMS Immunity	Compliance to IEC60601-1-2
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

Environmental	
Operating Temperature	0 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH
	Storage : 10 to 90% RH
Cooling	Natural Convection Cooling



Some Safety Agency Approvals may differ from what is shown here. Please contact factory!