


■ **Features**

- Power Rating: 40W
- Input Voltage: 120-277Vac ± 10%
- Constant current design
- Fixed output current(740mA-1670mA)
- Efficiency to 85%
- Dimmable with 0-10V dimmer
- UL Class 2
- OVP, OCP, SCP
- IP20
- 5-year warranty
- Metal case



\*Product images are for illustrative purposes only and may vary from actual design.

■ **Application**

- Indoor lights

■ **Model List**\*(See part number scheme for model number details)

Model Number	Input Voltage Range	Output Power	Output Voltage	Output Current Min.	Output Current Max.	Efficiency	Certification
LXWCD040S100SS-20	120~277Vac ± 10%	40W	27-54V	740mA	740mA	84%@120V 85%@240V 85%@277V	UL/-
LXWCD040S100SS-20	120~277Vac ± 10%	40W	25-50V	800mA	800mA	84%@120V 85%@240V 85%@277V	UL/-
LXWCD040S100SS-20	120~277Vac ± 10%	40W	22-44V	900mA	900mA	84%@120V 85%@240V 85%@277V	UL/-
LXWCD040S100SS-20	120~277Vac ± 10%	40W	21-42V	950mA	950mA	84%@120V 85%@240V 85%@277V	UL/-
LXWCD040S100SS-20	120~277Vac ± 10%	40W	20-40V	1000mA	1000mA	84%@120V 85%@240V 85%@277V	UL/-
LXWCD040S110SS-20	120~277Vac ± 10%	40W	18-36V	1100mA	1100mA	84%@120V 85%@240V 85%@277V	UL/cUL
LXWCD040S100SS-20	120~277Vac ± 10%	40W	17-33V	1200mA	1200mA	84%@120V 85%@240V 85%@277V	UL/cUL
LXWCD040S100SS-20	120~277Vac ± 10%	40W	17-31V	1300mA	1300mA	84%@120V 85%@240V 85%@277V	UL/cUL
LXWCD040S100SS-20	120~277Vac ± 10%	40W	14-29V	1400mA	1400mA	84%@120V 85%@240V 85%@277V	UL/cUL

**Technical Sales / Customer Service:** +1-818-338-7788 • Email: [sales@autec.com](mailto:sales@autec.com)  
31328 Via Colinas Suite 102 • Westlake Village, CA 91362 USA • [www.autec.com](http://www.autec.com)

LXWCD040S100SS-20	120~277Vac ± 10%	40W	13-27V	1500mA	1500mA	84%@120V 85%@240V 85%@277V	UL/cUL
LXWCD040S100SS-20	120~277Vac ± 10%	40W	13-25V	1600mA	1600mA	84%@120V 85%@240V 85%@277V	UL/cUL
LXWCD040S100SS-20	120~277Vac ± 10%	40W	12-24V	1670mA	1670mA	84%@120V 85%@240V 85%@277V	UL/cUL

## ■ Technical Data

Input voltage range	120~277Vac ± 10%
Frequency	50/60Hz
Power factor	>0.9 under 120-277Vac input with 80-100% load condition (for all output currents)
Inrush current	30A @ 230V
Max input current	0.44A @120V, 0.23A @240V and 0.20A @ 277V
THD	<20% under 120-277Vac input with 80-100% load condition (for all output currents)
Load regulation	± 2%
Line regulation	± 1%
Output tolerance	± 5% at full load condition
Turn-on delay time	<0.75s at full load condition
Overshoot	< 10% at full load condition
No load power consumption	< 2W
Ripple & Noise (pk-pk)	< 3%
Withstand voltage	Input to output, 2,800Vdc, 2mA
Leakage current	Maximum 0.5mA at 277Vac, 60Hz input
Protection	Over voltage protection: Hiccup mode. Protection will trigger when load voltage exceed specified output voltage and will auto recover after the fault mode is removed. Over current protection: Hiccup mode. Protection will trigger when load current exceed specified output current and will auto recover after the fault mode is removed. Short circuit protection: Hiccup mode. Protection will trigger when short circuit and will auto recover after the fault mode is removed.
Operating temperature	-40 to 60°C
Storage temperature	-40 to 85°C
Humidity	5% to 95%
MTBF	269,000 hours at 40°C ambient (~70°C case temp)
Life rating	80,000 hours at 120Vac input, 100% load and 60°C case temperature

**Technical Sales / Customer Service:** +1-818-338-7788 • Email: [sales@autec.com](mailto:sales@autec.com)  
31328 Via Colinas Suite 102 • Westlake Village, CA 91362 USA • [www.autec.com](http://www.autec.com)


■ Technical Data(cont.)

Maximum case Temperature	90°C
Length (L)	5.00" (127mm)
Width (W)	2.40" (62mm)
Height (H)	1.00" (25.4mm)
Mounting (M)	4.64" (118mm)
Weight	0.25kg
Packaging	0.25kg /unit; 50pcs /carton; 2,500pcs / pallet


■ Safety Compliance

UL/cUL	UL 8750, Type HL
CE	EN61347-1, EN61347-2-13
FCC, 47CFR Part 15	ANSI C63.4:2009 Class B (Consumer Limit)
EN61000-3-2	Harmonic Current Emissions Class C


■ Lifetime vs Case Temperature




■ Power Derating vs Case Temperature




■ Power Factor vs Load



■ **Efficiency vs Load**




■ **Wiring Diagram**



**Wire Specifications**

Wire Specifications	
Input	12", UL 1316 #18AWG (Black and White)
Output	12", UL 1569 #18AWG (with Non-Class 2 output) 12", UL 1316/1430 #22AWG (with Class 2 output) (Red and Blue)
Dimming	12", UL 1316/1430 #22AWG (Purple and Grey)

**Technical Sales / Customer Service:** +1-818-338-7788 • Email: [sales@autec.com](mailto:sales@autec.com)  
31328 Via Colinas Suite 102 • Westlake Village, CA 91362 USA • [www.autec.com](http://www.autec.com)



**\*Product images are for illustrative purposes only and may vary from actual design.**

**\*Specifications are subject to change without notice. Autec is not responsible for issues arising from errors or omissions.**